

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2003-167246

(43)Date of publication of application : 13.06.2003

(51)Int.Cl.

G02F 1/1335
G02B 5/30
G02F 1/1333
G02F 1/1343
H01L 21/3065

(21)Application number : 2001-370146

(71)Applicant : SEIKO EPSON CORP

(22)Date of filing : 04.12.2001


(72)Inventor : TAKEUCHI TETSUHIKO

(54) SUBSTRATE FOR LIQUID CRYSTAL DEVICE AND METHOD FOR MANUFACTURING THE SAME, LIQUID CRYSTAL DEVICE, PROJECTION TYPE DISPLAY DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a liquid crystal device which incorporates a polarizer with a high extinction ratio and has high durability.

SOLUTION: In the liquid crystal device, a liquid crystal layer 50 is held between a pair of substrates. A pixel electrode 9 comprising a structure birefringence body having a plurality of light reflection bodies 9a arranged in a stripe shape at a pitch smaller than light wavelength incident on the liquid crystal layer 50 and a gas layer 9b formed in a space between two adjacent light reflection bodies, is formed on a TFT-arrayed substrate 10. The structure birefringence body functions as a pixel electrode and functions as a polarizer at the side of the TFT-arrayed substrate at the same time. This constitution eliminates an external light absorption type polarizer used conventionally, and improves the durability.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the

AN

examiner's decision of rejection or application
converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of
rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

File 347:JAPIO Nov 1976-2005/Aug(Updated 051205)
(c) 2005 JPO & JAPIO

Set Items Description

? e pn=jp 2003167246

Ref	Items	Index-term
E1	1	PN=JP 2003167244
E2	1	PN=JP 2003167245
E3	1	*PN=JP 2003167246
E4	1	PN=JP 2003167247
E5	1	PN=JP 2003167248
E6	1	PN=JP 2003167249
E7	1	PN=JP 2003167250
E8	1	PN=JP 2003167251
E9	1	PN=JP 2003167252
E10	1	PN=JP 2003167253
E11	1	PN=JP 2003167254
E12	1	PN=JP 2003167255

Enter P or PAGE for more

? s e3
S1 1 PN='JP 2003167246'
? t 1/9/1

1/9/1
DIALOG(R)File 347:JAPIO
(c) 2005 JPO & JAPIO. All rts. reserv.

07673384 **Image available**
SUBSTRATE FOR LIQUID CRYSTAL DEVICE AND METHOD FOR MANUFACTURING THE SAME,
LIQUID CRYSTAL DEVICE, PROJECTION TYPE DISPLAY DEVICE

PUB. NO.: 2003-167246 [JP 2003167246 A]
PUBLISHED: June 13, 2003 (20030613)
INVENTOR(s): TAKEUCHI TETSUHIKO
APPLICANT(s): SEIKO EPSON CORP
APPL. NO.: 2001-370146 [JP 2001370146]
FILED: December 04, 2001 (20011204)
INTL CLASS: G02F-001/1335; G02B-005/30; G02F-001/1333; G02F-001/1343;
H01L-021/3065

ABSTRACT

PROBLEM TO BE SOLVED: To provide a liquid crystal device which incorporates a polarizer with a high extinction ratio and has high durability.

SOLUTION: In the liquid crystal device, a liquid crystal layer 50 is held between a pair of substrates. A pixel electrode 9 comprising a structure birefringence body having a plurality of light reflection bodies 9a arranged in a stripe shape at a pitch smaller than light wavelength incident on the liquid crystal layer 50 and a gas layer 9b formed in a space between two adjacent light reflection bodies, is formed on a TFT-arrayed substrate 10. The structure birefringence body functions as a pixel electrode and functions as a polarizer at the side of the TFT-arrayed substrate at the same time. This constitution eliminates an external light absorption type polarizer used conventionally, and improves the durability

AN

COPYRIGHT: (C) 2003, JPO

? logoff

18jan06 12:18:24 User147493 Session D3699.2

Sub account: 0717.2053-001 RCH